

# PRODUCT DATASHEET

## DST STICK 11 W/2700 K 220...240 V E27

OSRAM DULUX® STICK | Compact fluorescent integrated, stick shape



### Areas of application

- High-quality domestic and professional environments
- General illumination
- Outdoor use in enclosed and ventilated luminaires only

### Product benefits

- Excellent price/performance ratio
- Great variety of light colors

### Product features

- Good quality of light; color rendering index  $R_a \geq 80$ ; constant chromaticity
- Average life: 10,000 h




**TECHNICAL DATA**

**Electrical data**

Nominal wattage	11 W
Construction wattage	11.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	51 W
Nominal current	110 mA
Type of current	AC
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Power factor $\lambda$	$\geq 0.55$

**Photometrical data**

Luminous flux	600 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	$\geq 80$
Light color	827



**Light technical data**

Warm-up time (60 %)	$< 40.00$ s
Starting time	$\leq 0.3$ s

**Dimensions & Weight**

Overall length	126.00 mm
Diameter	43.00 mm

Maximum diameter	43 mm
Product weight	55.00 g

### Temperatures & operating conditions

Ambient temperature range	-10...+50 °C
---------------------------	--------------

### Lifespan

Nominal lamp life time	6000 h
Number of switching cycles	30000
Lumen maintenance at end of serv	0.70

### Additional product data

Base (standard designation)	E27
Mercury content	2.0 mg
Mercury-free	No

### Capabilities

Dimmable	No
----------	----

### Certificates & Standards

Energy efficiency class	A
Energy consumption	11.00 kWh/1000h

### Country-specific categorizations

ILCOS	FBT-11/827-220/240-E27
Order reference	DULUX STICK 11W

### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	125.00 mm
Height	43.00 mm
Width	43.00 mm

### Safety advice

- In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)
- Not for use with external dimmers or electronic switches.

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321363794	Folding box 1	131 mm x 47 mm x 47 mm	102.13 g	0.29 dm <sup>3</sup>
4008321363800	Shipping box 10	240 mm x 143 mm x 139 mm	957.33 g	4.77 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.