

# PRODUCT DATASHEET

## L 32 W/827 G10Q

LUMILUX® T9 C | Circular fluorescent lamps 29 mm, with G10Q base



---

### Areas of application

- Public buildings
- Restaurants
- Industry
- Shops
- Supermarkets and department stores
- Hotels

---

### Product benefits

- Excellent uniform illumination with no shadows

---

### Product features

- Good color rendering index
- Single-ended round fluorescent lamp
- Dimmable




## TECHNICAL DATA

### Electrical data

Nominal wattage	32 W
Construction wattage	34.10 W
Nominal voltage	84 V
Nominal current	0.45 A

### Photometrical data

Luminous flux	2100 lm
Luminous efficacy	62 lm/W
Light color (designation)	LUMILUX INTERNA
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Rated LLMF at 2,000 h	0.80
Rated LLMF at 4,000 h	0.74
Rated LLMF at 6,000 h	0.72
Rated LLMF at 8,000 h	0.70



### Dimensions & Weight

Overall length	299.00 mm
Diameter	305 mm
Tube diameter	29 mm
Product weight	176.00 g

### Lifespan

Nominal lamp life time	9000 h
------------------------	--------

Service life	6300 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000	0.95
Rated lamp survival factor at 6,000	0.83
Rated lamp survival factor at 8,000 h	0.62
Lifespan B50	9000 h

### Additional product data

Base (standard designation)	G10q
Mercury content	4.8 mg
Design / version	LUMILUX version

### Capabilities

Dimmable	Yes
----------	-----

### Certificates & Standards

Energy efficiency class	G
Energy consumption	35.00 kWh/1000h

### Country-specific categorizations

ILCOS	FSC-32/827-E-G10q-29/305
Order reference	L 32W/827 C G10

### Energy labelling regulation data acc EU 2019/2015

Lighting technology used	OTHER_FL
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G10q
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	299.00 mm
Height	305 mm

Width	305 mm
Chromaticity coordinate x	0,463
Chromaticity coordinate y	0,420
Beam angle	SPHERE_360
EPREL ID	546414
Model number	AC34189




## EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic and conventional control gears

## Safety advice

- In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

## DOWNLOAD DATA

DOWNLOAD DATA	
	Certificates EAC N RU D-DE.PA01.B.25780_21 23.07.2021-22.07.2026 - FL Special
	Certificates EAC RU C-DE HA10.B.00671 16 08 2018 15 07 2023 Expert Sertifikaciya FL
	Declarations of conformity EC Declaration of Conformity - 2021 9C1-4077059-EN-01 - T9 C

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321581129	Sleeve 1	309 mm x 38 mm x 306 mm	315.60 g	3.59 dm <sup>3</sup>
4008321581136	Shipping box 12	452 mm x 320 mm x 323 mm	4228.20 g	46.72 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.