

PRODUCT DATASHEET

L 15 W/830

LUMILUX® T8 | Tubular fluorescent lamps 26 mm, with G13 bases



Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

Product benefits

- Proven lamp technology

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable




TECHNICAL DATA

Electrical data

| | |
|----------------------|---------|
| Nominal wattage | 15 W |
| Construction wattage | 14.90 W |
| Nominal voltage | 55 V |
| Nominal current | 0.31 A |

Photometrical data

| | |
|---------------------------|--------------------|
| Luminous flux | 950 lm |
| Luminous efficacy | 64 lm/W |
| Light color (designation) | LUMILUX Warm White |
| Color temperature | 3000 K |
| Color rendering index Ra | ≥80 |
| Light color | 830 |
| Rated LLMF at 2,000 h | 0.96 |
| Rated LLMF at 4,000 h | 0.94 |
| Rated LLMF at 6,000 h | 0.92 |
| Rated LLMF at 8,000 h | 0.91 |
| Rated LLMF at 12,000 h | 0.91 |
| Rated LLMF at 16,000 h | 0.90 |
| Rated LLMF at 20,000 h | 0.89 |



Dimensions & Weight

| | |
|---|-----------|
| Overall length | 451.60 mm |
| Length with base excl. base pins/connection | 438,00 mm |
| Diameter | 26,0 mm |
| Tube diameter | 26 mm |

| | |
|----------------|---------|
| Product weight | 60.00 g |
|----------------|---------|

Lifespan

| | |
|--|-----------------------|
| Nominal lamp life time | 20000 h |
| Service life | 16000 h ¹⁾ |
| Rated lamp survival factor at 2,000 h | 0.99 |
| Rated lamp survival factor at 4,000 | 0.99 |
| Rated lamp survival factor at 6,000 | 0.99 |
| Rated lamp survival factor at 8,000 h | 0.99 |
| Rated lamp survival factor at 12,000 h | 0.99 |
| Rated lamp survival factor at 16,000 | 0.90 |
| Rated lamp survival factor at 20,000 h | 0.50 |
| Lifespan B50 | 20000 h |

¹⁾ With preheat ECG

Additional product data

| | |
|-----------------------------|--------|
| Base (standard designation) | G13 |
| Mercury content | 3.0 mg |

Capabilities

| | |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

Certificates & Standards

| | |
|-------------------------|-----------------|
| Energy efficiency class | G |
| Energy consumption | 15.00 kWh/1000h |

Country-specific categorizations

| | |
|-----------------|------------------------|
| ILCOS | FD-15/830-E-G13-26/438 |
| Order reference | L 15W/830 |

Energy labelling regulation data acc EU 2019/2015





| | |
|---|----------|
| Lighting technology used | OTHER_FL |
| Non-directional or directional | NDLS |
| Mains or non-mains | NMLS |
| Light source cap-type (or other electric interface) | G13 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |

| | |
|------------------------------------|--------------|
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | No |
| Length | 451.60 mm |
| Height | 26,0 mm |
| Width | 26,0 mm |
| Chromaticity coordinate x | 0,440 |
| Chromaticity coordinate y | 0,403 |
| Beam angle | SPHERE_360 |
| EPREL ID | 546353 |
| Model number | AC34140 |

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

| DOWNLOAD DATA | |
|--|---|
|  | Declarations of conformity EC Declaration of Conformity - 2021 9C1-4071456-EN-01 - T8 |
|  | Advertisements 335262_Light color and lumen overview / Lichtfarben- und Lumenübersicht |
|  | Advertisements 333507_SKYWHITE-en |
|  | Advertisements 333819_Light in its third dimension.The biological aspect of lighting design for better |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4050300446028 | Sleeve 1 | 452 mm x 27 mm x 27 mm | 73.00 g | 0.33 dm ³ |
| 4050300446035 | Shipping box 25 | 396 mm x 230 mm x 145 mm | 2158.00 g | 13.21 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.