

# PRODUCT DATASHEET

## PLANTASTAR 400 W E40

PLANTASTAR®-T | High-pressure sodium vapor lamps for open and enclosed luminaires



---

### Areas of application

- Greenhouses
- Suitable for growth of fruit due to emission of photosynthesis optimised light
- Application only in suitable luminaires

---

### Product benefits

- Shorter production times
- Control over blossoming

---

### Product features



- Provides light for the photosynthesis in plants
- Photon flux: > 90 % after 12,000 h
- High-pressure sodium lamp especially for greenhouse lighting

## TECHNICAL DATA

### Electrical data

Nominal wattage	400 W
Nominal voltage	100 V
Ignition voltage	4.0/5.0 kVp <sup>1)</sup>
Nominal current	4.52 A
PFC capacitor at 50 Hz	45 µF

<sup>1)</sup> Minimum / Maximum

### Photometrical data

Luminous flux	56500 lm
Luminous efficacy	136 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.98
Rated LLMF at 4,000 h	0.97
Rated LLMF at 6,000 h	0.96
Rated LLMF at 8,000 h	0.95
Rated LLMF at 12,000 h	0.94
Rated LLMF at 16,000 h	0.94
Rated LLMF at 20,000 h	0.94
UV protection	No

### Dimensions & Weight

Overall length	285.00 mm
Length	285.00 mm
Light center length (LCL)	175,0 mm
Diameter	47 mm
Product weight	150.00 g

### Temperatures & operating conditions

Maximum permitted outer bulb temperature	400 °C
Maximum permitted base edge temperature	250 °C

### Lifespan

Nominal lamp life time	32000 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000	0.99
Rated lamp survival factor at 6,000	0.98
Rated lamp survival factor at 8,000 h	0.97
Rated lamp survival factor at 12,000 h	0.96
Rated lamp survival factor at 16,000	0.95
Rated lamp survival factor at 20,000 h	0.93
Lifespan B10	24000 h
Lifespan B5	20000 h
Lifespan B50	32000 h

### Additional product data

Base (standard designation)	E40
Mercury content	21.6 mg
Design / version	Clear
Product remark	Not for general lighting

### Capabilities

Dimmable	No
Burning position	Any
Enclosed luminaire required	No
Hot restart	No



### Certificates & Standards

Energy consumption	417.00 kWh/1000h
--------------------	------------------

### Country-specific categorizations

ILCOS	ST-400-H/E-E40-47/285
Order reference	PLANTASTAR 400W

### DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction High Intensity Discharge Lamp UI
	Certificates EAC RU C-DE.AYA46.B.85891 29.06.2018-28.06.2023 ROSTEST-Moskva - HPS

## DOWNLOAD DATA



Certificates  
EAC N RU D-DE.MU62.B.00936\_20 06.03.2020-05.03.2025 Prommash Test - HPS



Declarations of conformity  
EC Declaration of Conformity - 2021 9C1-4083706-EN-00 - HPS PLANTA



Advertisements  
505913\_Light is growth- PLANTASTAR (GB)



Advertisements  
505914\_Light is growth- PLANTASTAR (DE)

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300620084	Sleeve 1	52 mm x 52 mm x 325 mm	192.00 g	0.88 dm <sup>3</sup>
4050300620091	Shipping box 12	266 mm x 216 mm x 342 mm	2694.00 g	19.65 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.