

PRODUCT DATASHEET ST 151 LONGLIFE

Starters for series operation at 230 V AC (ST 151, ST 172) | Starters for series operation at 230 V AC

Product features

- Temperature range for reliable cut-out: -20...+80 °C



November 21, 2021, 02:29:22 ST 151 LONGLIFE

TECHNICAL DATA

Electrical data

| Nominal wattage | 22.00 W |
|-----------------|----------|
| Nominal voltage | 220240 V |
| Mains frequency | 50/60 Hz |

Dimensions & Weight

| Diameter | 21,5 mm |
|----------------|---------|
| Product weight | 6.43 g |

Additional product data

| Mercury content | 0.0 mg | |
|-----------------|--|--|
| Product remark | Starters are available in two different designs, with identical technical features | |
| | | |

Capabilities

| | Dimmable | No |
|--|----------|----|
|--|----------|----|

Country-specific categorizations

| Order reference | ST 151 LONGLIFE |
|-----------------|-----------------|
| | |

Energy labellling regulation data acc EU 2019/2015

| Length | 40.30 mm |
|--------|----------|
| Height | 21,5 mm |
| Width | 21.50 mm |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300854083 | Unpacked 1 | 37 mm x 19 mm x 20 mm | 6.64 g | 0.01 dm³ |
| 4050300797885 | Tray 25 | 111 mm x 59 mm x 111 mm | 169.46 g | 0.73 dm ³ |
| 4050300797892 | Shipping box 400 | 227 mm x 179 mm x 227 mm | 2796.25 g | 9.22 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.