

PRODUCT DATASHEET

P MR16 50 36 ° 7.2 W/4000 K GU5.3

PARATHOM® MR16 | Low-voltage LED reflector lamps MR16 with retrofit pin base



Areas of application

- Shops and exhibition rooms
- Domestic applications
- Commercial applications
- Accent lighting
- Outdoor use in outdoor luminaires only (minimum IP65)

Product benefits

- Quick, simple and safe replacement without rewiring
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Low maintenance costs thanks to long lifetime
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time

Product features

- LED alternative to low voltage halogen lamps
- High color consistency: ≤ 6 SDCM
- Not dimmable
- Base: GU5.3
- Lamp made of glass



- Good quality of light; color rendering index $R_a \geq 80$
- Lifetime: up to 15,000 h


TECHNICAL DATA

Electrical data

| | |
|--|--------|
| Nominal wattage | 7.2 W |
| Construction wattage | 7.20 W |
| Nominal voltage | 12 V |
| Claimed equiv. conventional lamp power | 50 W |
| Nominal current | 880 mA |
| Type of current | AC |
| Inrush current | 13.3 A |
| Max. lamp no. on circuit break. 10 A (B) | 20 |
| Max. lamp no. on circuit break. 16 A (B) | 33 |
| Power factor λ | > 0.50 |

Photometrical data


| | |
|---|--------------|
| Luminous intensity | 1430 cd |
| Luminous flux | 621 lm |
| Nominal useful luminous flux 90° | 621 lm |
| Luminous efficacy | 86 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Cool White |
| Color temperature | 4000 K |
| Color rendering index Ra | ≥ 80 |
| Light color | 840 |
| Standard deviation of color matching | ≤ 6 sdc |
| Rated peak intensity | 1430 cd |
| Rated LLMF at 6,000 h | 0.80 |



Light technical data

| | |
|------------------------------------|----------|
| Beam angle | 36 ° |
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |
| Rated beam angle (half peak value) | 36.00 ° |

Dimensions & Weight



| | |
|------------------|----------|
| Overall length | 53.00 mm |
| Diameter | 51.00 mm |
| Maximum diameter | 51 mm |
| Product weight | 65.00 g |

Temperatures & operating conditions

| | |
|--------------------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
| Maximum temperature at tc test point | 90 °C |

Lifespan

| | |
|-------------------------------------|---------|
| Nominal lamp life time | 15000 h |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of serv | 0.70 |
| Rated lamp survival factor at 6,000 | ≥ 0.90 |

Additional product data

| | |
|-----------------------------|--|
| Base (standard designation) | GU5.3 |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & Standards

| | |
|--|------------------|
| Energy efficiency class | A+ ¹⁾ |
| Energy consumption | 8.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE / EAC |
| Photobiological safety group acc. to EN62778 | RG1 |

¹⁾ Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

| | |
|-----------------|----------------------------|
| ILCOS | DRR-7,2/840-12-GU5,3-50/36 |
| Order reference | LPMR165036 7,2W |




Energy labelling regulation data acc EU 2019/2015

| | |
|---|----------|
| Light source cap-type (or other electric interface) | GU5.3 |
| Length | 53.00 mm |
| Height | 51.00 mm |
| Width | 51.00 mm |

EQUIPMENT / ACCESSORIES

- Equipped with high-power LEDs

DOWNLOAD DATA

| DOWNLOAD DATA | |
|--|---|
|  | PRODUCT DATASHEET P MR16 50 36 7.2 W 4000K GU5.3 DATASHEET |
|  | IES file (IES) AC07587_MR16 50 7,2W12V GU5 |
|  | LDT file (Eulumdat) AC07587_MR16 50 7,2W12V GU5 |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4052899957824 | Folding box 1 | 49 mm x 49 mm x 62 mm | 72.00 g | 0.15 dm ³ |
| 4052899958524 | Shipping box 10 | 255 mm x 107 mm x 72 mm | 745.00 g | 1.96 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee
- Further information see www.ledvance.com/low-voltage-ledlamps

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.