

# PRODUCT DATASHEET

## HQI-E 400 W/N CL

POWERSTAR HQI®-E clear | Metal halide lamps with quartz technology for enclosed luminaires



### Areas of application

- Factories and workshops
- Exhibition halls and trade fairs
- Sports halls and multi-purpose halls
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

### Product benefits

- E40 screw base for simple lamp handling
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

### Product features

- POWERSTAR® quartz technology
- Light color: neutral white (N)



## TECHNICAL DATA


### Electrical data

Nominal wattage	440 W
Construction wattage	450.00 W
Nominal voltage	124 V
Ignition voltage	4.0/5.0 kVp <sup>1)</sup>
Nominal current	3.9 A
PFC capacitor at 50 Hz	45 µF

<sup>1)</sup> Minimum / Maximum

### Photometrical data

Luminous flux	42000 lm
Luminous efficacy	93 lm/W
Color temperature	4000 K
Color rendering index Ra	60
Light color	640
Rated LLMF at 2,000 h	0.86
Rated LLMF at 4,000 h	0.75
Rated LLMF at 6,000 h	0.68
Rated LLMF at 8,000 h	0.64
UV protection	Yes



### Dimensions & Weight

Overall length	290.00 mm
Light center length (LCL)	198,0 mm
Diameter	120,0 mm
Product weight	248.7 g

### Temperatures & operating conditions

Maximum permitted outer bulb temperature	500 °C
Maximum permitted base edge temperature	250 °C

### Lifespan

Nominal lamp life time	9000 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000	0.99
Rated lamp survival factor at 6,000	0.70
Lifespan B50	9000 h

### Additional product data

Base (standard designation)	E40
Mercury content	60.0 mg
Design / version	Clear
Product remark	With NAV® control gear

### Capabilities

Dimmable	No
Burning position	h45
Enclosed luminaire required	Yes
Hot restart	No

### Certificates & Standards

Energy efficiency class	F
Energy consumption	450.00 kWh/1000h

### Country-specific categorizations





ILCOS	MC/UB-400/637-H/E/SL-E40-120/290
Order reference	HQI-E 400/N E40

### Energy labelling regulation data acc EU 2019/2015

Lighting technology used	MH
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	E40
Connected light source (CLS)	No
Color-tuneable light source	No

Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	290.00 mm
Height	120,0 mm
Width	120,0 mm
Chromaticity coordinate x	0,380
Chromaticity coordinate y	0,395
Beam angle	SPHERE_360
EPREL ID	546560
Model number	AC34334

## DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction High Intensity Discharge Lamp UI
	Certificates EAC RU C-DE.AYA46.B.16087_20 13.10.2020-12.10.2025 Rostest-Moskva - MH single capped
	Certificates EAC N RU D-DE.MU62.B.00932_20 06.03.2020-05.03.2025 Prommash Test - MH
	Declarations of conformity EC Declaration of Conformity - 2021 9C1-4072118-EN-01 - HQI

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075039780	Round wrap 1		344.17 g	
4058075039797	Shipping box 12	545 mm x 410 mm x 410 mm	5870.00 g	91.61 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.