

PRODUCT DATASHEET

NAV-T 250 W SUPER XT

VIALOX® NAV®-T SUPER XT | High-pressure sodium vapor lamps for open and enclosed luminaires



Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires
- Alternative to sodium twin arc lamps

Product benefits

- Very long lifetime
- Very high luminous efficacy
- Extended service time (lamp replacement cycle): 8 years (at approx. 11 h/day)
- Very good luminous flux maintenance throughout the life of the lamp
- Optimum energy efficiency on POWERTRONIC® PTo 3DIM ECGs



Product features

- Lamp survival rate: 95 % after 28,000 h burning time
- Lamp maintenance factor: ≥ 80 % after 24,000 h burning time (according to DIN 13201)
- Dimmable on conventional control gears and electronic control gears

TECHNICAL DATA


Electrical data

Nominal wattage	250 W
Construction wattage	256.40 W
Nominal voltage	100 V
Ignition voltage	3.3/5.0 kVp ¹⁾
Nominal current	2.95 A
PFC capacitor at 50 Hz	32 µF

¹⁾ Minimum / Maximum

Photometrical data

Luminous flux	33200 lm
Luminous efficacy	129 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.98
Rated LLMF at 4,000 h	0.97
Rated LLMF at 6,000 h	0.96
Rated LLMF at 8,000 h	0.95
Rated LLMF at 12,000 h	0.94
Rated LLMF at 16,000 h	0.94
Rated LLMF at 20,000 h	0.94
UV protection	No



Dimensions & Weight

Overall length	257.00 mm
----------------	-----------

Light center length (LCL)	158,0 mm
Diameter	47.00 mm
Product weight	135.00 g

Temperatures & operating conditions

Maximum permitted outer bulb temperature	400 °C
Maximum permitted base edge temperature	250 °C

Lifespan

Nominal lamp life time	48000 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000	0.99
Rated lamp survival factor at 6,000	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.99
Rated lamp survival factor at 20,000 h	0.99
Lifespan B10	34000 h
Lifespan B5	28000 h
Lifespan B50	48000 h

Additional product data

Base (standard designation)	E40
Mercury content	21.6 mg
Design / version	Clear
Product remark	Important: Before replacing for NAV Standard lamps in existing installations, check that the igniters are suitable

Capabilities

Dimmable	Yes ¹⁾
Burning position	Any
Enclosed luminaire required	No
Hot restart	No

¹⁾ In combination with POWERTRONIC PTo

Certificates & Standards

Energy efficiency class	E
-------------------------	---

Energy consumption	257.00 kWh/1000h
--------------------	------------------




Country-specific categorizations

ILCOS	ST-250-H/E/SL-E40-47/257
Order reference	NAV-T 250WSUPER

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	HPS
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	E40
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	257.00 mm
Height	47.00 mm
Width	47.00 mm
Chromaticity coordinate x	0,535
Chromaticity coordinate y	0,420
Beam angle	SPHERE_360
EPREL ID	546601
Model number	AC34396

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction High Intensity Discharge Lamp UI
	Certificates EAC RU C-DE.AYA46.B.85891 29.06.2018-28.06.2023 ROSTEST-Moskva - HPS
	Certificates EAC N RU D-DE.MU62.B.00936_20 06.03.2020-05.03.2025 Prommash Test - HPS

DOWNLOAD DATA



Declarations of conformity
EC Declaration of Conformity - 2021 9C1-4077887-EN-00 - HPS

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075803619	Sleeve 1	52 mm x 52 mm x 325 mm	166.00 g	0.88 dm ³
4058075803749	Shipping box 12	266 mm x 216 mm x 342 mm	2424.00 g	19.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.