

# PRODUCT DATASHEET

## LEDinestra 25 200 ° 3.5 W/2700 K S14d

LEDinestra® | Tubular LED lamps



### Areas of application

- Ideal for mirror lighting
- Hotels, restaurants
- Domestic applications
- Outdoor applications only in suitable luminaires

### Product benefits

- Long lifetime of up to 15,000 h
- Low energy consumption
- Good color rendering

### Product features

- LED alternative to tubular incandescent lamps
- Uniform illumination
- Mercury-free lamps
- Bulb made from glass



## TECHNICAL DATA

### Electrical data

Nominal wattage	3.5 W
Construction wattage	3.50 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	25 W
Nominal current	16 mA
Type of current	AC
Inrush current	0.6 A
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Max. lamp no. on circuit break. 10 A (B)	600
Max. lamp no. on circuit break. 16 A (B)	1000
Power factor $\lambda$	> 0.80

### Photometrical data

Luminous flux	260 lm
Nominal useful luminous flux 90°	260 lm
Luminous efficacy	74 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdc <sub>m</sub>
Rated LLMF at 6,000 h	0.80

### Light technical data

Beam angle	200 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s
Rated beam angle (half peak value)	200.00 °

### Dimensions & Weight



Overall length	300.00 mm
Length with base excl. base pins/connection	300,00 mm
Diameter	29 mm
Maximum diameter	29 mm
Product weight	75.00 g

### Temperatures & operating conditions

Ambient temperature range	0...+30 °C
Maximum temperature at tc test point	50 °C

### Lifespan

Nominal lamp life time	15000 h
Number of switching cycles	100000
Lumen maintenance at end of serv	0.70
Rated lamp survival factor at 6,000	≥ 0.90

### Additional product data

Base (standard designation)	S14d
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted

### Capabilities

Dimmable	No
----------	----

### Certificates & Standards

Energy efficiency class	A+ <sup>1)</sup>
Energy consumption	4.00 kWh/1000h
Type of protection	IP20
Standards	CE
Photobiological safety group acc. to EN62778	RG0

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)





## Country-specific categorizations

ILCOS	DRL/F-3,5/827-230-S14D-29/300
Order reference	LEDINESTRA25 3,

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	S14d
Length	300.00 mm
Height	29 mm
Width	29 mm

## DOWNLOAD DATA

DOWNLOAD DATA	
	PRODUCT DATASHEET LEDInestra 25 200 3.5 W 2700K S14d DATASHEET
	Declarations of conformity EC Declaration LEDInestra-non_DIM
	IES file (IES) AC18701_LEDINESTRA 3,5W 827 230V FR
	LDT file (Eulumdat) AC18701_LEDINESTRA 3,5W 827 230V FR

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075817753	Folding box 1	33 mm x 50 mm x 307 mm	113.00 g	0.51 dm <sup>3</sup>
4058075817760	Shipping box 10	370 mm x 215 mm x 155 mm	1102.00 g	12.33 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

