## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or | r trade mark: | PHILIPS |
|--------------------|---------------|---------|
|--------------------|---------------|---------|

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| Model identifier: | 8711500622655 |
|-------------------|---------------|
|-------------------|---------------|

| _    | •   |        |       |     |
|------|-----|--------|-------|-----|
| Type | Λt  | liaht  | COLIF | co. |
| IVDE | UI. | IIKIIL | 30ui  | LC. |

| Lighting technology used:     | other FL | Non-directional or directional: | NDLS |
|-------------------------------|----------|---------------------------------|------|
| Light source cap-type         | G13      |                                 |      |
| (or other electric interface) |          |                                 |      |
| Mains or non-mains:           | NMLS     | Connected light source (CLS):   | No   |
| Colour-tuneable light source: | No       | Envelope:                       | -    |
| High luminance light source:  | No       |                                 |      |
| Anti-glare shield:            | No       | Dimmable:                       | Yes  |
| Product parameters            |          |                                 |      |

| Parameter                            |  | Value                     | Parameter  | Value        |
|--------------------------------------|--|---------------------------|--|--------------|
|                                      |  | General product p         | arameters:   |              |
|                                      | mption in on-<br>100 h), rounded<br>st integer                             | 31                        | Energy efficiency<br>class   | G            |
| indicating if it r<br>in a sphere (3 | us flux (фuse),<br>efers to the flux<br>60º), in a wide<br>n a narrow cone | 2 400 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000        |
| On-mode prespressed in W             | oower (P <sub>on</sub> ),  | 30,2                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00         |
| for CLS, expres                      | dby power (P <sub>net</sub> )<br>ssed in W and<br>second decimal           | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 81           |
| Outer                                | Height   | 909                       | Spectral power   | See image    |
| dimensions                           | Width  | 28                        | distribution in the  | in last page |
| without                              | Depth  | 28                        |  |              |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800<br>nm, at full-load |       |
|--|---|-------|
| Claim of equivalent power <sup>(a)</sup>   | - If yes, equivalent power (W)          | -     |
|  | Chromaticity coordinates (x and y)      | 0,380 |

(a)'-': not applicable; (b)'-': not applicable;

