

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** PHILIPS

**Supplier's address:** Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

**Model identifier:** 8718291651673

## Type of light source:

|   |      |                                 |     |
|---|------|---------------------------------|-----|
| Lighting technology used:                           | MH   | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | E27  |                                 |     |
| Mains or non-mains:                                 | NMLS | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | No   | Envelope:                       | No  |
| High luminance light source:                        | No   |                                 |     |
| Anti-glare shield:                                  | No   | Dimmable:                       | No  |

## Product parameters

| Parameter  | Value                      | Parameter  | Value  |
|--|----------------------------|--|--|
| <b>General product parameters:</b>   |                            |  |  |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 74                         | Energy efficiency class  | G  |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 4 500 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 200  |
| On-mode power ( $P_{on}$ ), expressed in W   | 73,2                       | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                          | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 92   |
| Outer dimensions without   | Height                     | 123  | Spectral power distribution in the<br>See image in last page |
|  | Width                      | 97   |  |
|  | Depth                      | 97   |  |

|   |        |  |       |
|---|--------|--|-------|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) |        | range 250 nm to 800 nm, at full-load                               |       |
| Claim of equivalent power <sup>(a)</sup>  | -      | If yes, equivalent power (W)                                       | -     |
|   |        | Chromaticity coordinates (x and y)                                 | 0,371 |
| <b>Parameters for directional light sources:</b>  |        |  |       |
| Peak luminous intensity (cd)  | 13 500 | Beam angle in degrees, or the range of beam angles that can be set | 30    |

(a)- : not applicable;

(b)- : not applicable;

