## **Product Information Sheet**

without

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources		, , ,	_	
Supplier's name	e or trade mark:	PHILIPS		
Supplier's addre	ess: Customer Ca	re Philips, I.B.R.S./C	.C.R.I. /Numéro 10461,	5600VB Eindhoven, NL
Model identifie	r: 871829124186	57		
Type of light so	urce:			
Lighting technology used:		МН	Non-directional or directional:	DLS
Light source cap-type		E27		
(or other electric interface)				
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	No
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	No
		Product parai	meters	
Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		74	Energy efficiency class	G
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		4 500 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P <sub>on</sub> ), expressed in W		73,2	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	92
Outer	Height	123	Spectral power	See image
dimensions	Width	97	distribution in the	in last page

97

separate control gear, lighting control parts		range 250 nm to 800 nm, at full-load				
and non- lighting						
control parts, if any (millimetre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,434			
Parameters for directional light sources:						
Peak luminous intensity (cd)	61 000	Beam angle in degrees, or the range of beam angles that can be set	10			

(a)'-': not applicable; (b)'-': not applicable;

