
TUNGSRAM

Innovation is our heritage EST. 1896






Discharge - Single Ended Cold Start CSR700/2/SE 93106385

Product information

Compact, single ended metal halide cold start lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering Ra from 70 - 90+- High CCT 7200 - 9000 K with superior colour stability -Universal burn position -Dimmable with stable colour- High efficiency with excellent lumen maintenance.

Application areas





Product data

Product Code	93106385
Light Center Length [mm]	75
Bulb Shape	Tubular
Bulb Finish	Clear
Bulb Diameter [mm]	28.6
Maximum Overall Length [mm]	155
Arc Gap	7.5
Net weight per piece [g]	190
Gross weight per piece [g]	213
Operating position	U - Universal
Brand	Tungsram
Cap/Base	G22

Performance data

Colour Code	765
Rated Lumens [lm]	55000
Weighted energy consumption [kWh/1000h]	770.0
Nominal chromaticity coordinate X	0.312
Nominal chromaticity coordinate Y	0.325
Nominal correlated colour temperature (CCT) [K]] 6500	
Nominal lumens [lm]	55000
Colour Rendering Index (CRI) [Ra]	70

Electrical data

Rated power [W]	700.0
Lamp Current [A]	10
Dimming Capability	No
Ballast Required	Yes
Nominal power [W]	700
Nominal lamp voltage [V]	70

Logistic data

DUN Code	15994100012457
EAN Code	5994100012450
Pack Quantity	10
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	130 UK
Layer quantity UK	130
Pallet quantity UK (PC)	780
Outer case size	370 x 154 x 230 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP)

Disclaimer

Special Purpose Lamp, Not suited for household illumination



Tungsram is a registered trademark of Tungsram Operations Kft.

tungsram.com

We in Tungsram Operations Kft. are constantly developing and improving our products. For this reason, all product descriptions in this catalogue are intended as a general guide, and we may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, Tungsram cannot accept any liability arising from the reliance on such data to the extent permitted by law.