TUNGSRAM

Innovation is our heritage EST. 1896







Discharge - Single Ended Hot Restrike CSR12000/SE/HR/UV-C 93106397

Product information

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance

Application areas



Film and Broadcast







Discharge - Single Ended Hot Restrike CSR12000/SE/HR/UV-C

93106397

Product data

Product Code	93106397
Light Center Length [mm]	255
Bulb Shape	Tubular
Bulb Finish	Clear
Net weight per piece [g]	1200
Gross weight per piece [g]	2600
Operating position	U - Universal
Brand	Tungsram
Cap/Base	G38

Performance data

Rated Lumens [lm]	1150000
Weighted energy consumption [kWh/1000h]	13200.0
Nominal chromaticity coordinate X	0.3
Nominal chromaticity coordinate Y	0.3
Nominal correlated colour temperature (CCT) [K]]	6000
Nominal lumens [lm]	1150000
Colour Rendering Index (CRI) [Ra]	90

Electrical data

Rated power [W]	12000.0
Dimming Capability	Yes
Nominal power [W]	12000
Nominal lamp voltage [V]	160



Discharge - Single Ended Hot Restrike

SR12000/SE/HR/UV-C **93106397**

Logistic data

DUN Code	15994100012464
EAN Code	5994100012467
Pack Quantity	4
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	8 UK
Layer quantity UK	8
Pallet quantity UK (PC)	8
Outer case size	540 x 540 x 610 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Disclaimer

Special Purpose Lamp, Not suited for household illumination